

Graph algorithms recap through the complexity lens

Lesson 88 · Module 7 — Algorithms, Complexity & Epilogue · Discrete Mathematics · daily-maths.uk/discrete

Practice problems

1. A graph has $V = 5000$ vertices and $E = 20000$ edges. Calculate the approximate number of operations for B-F-S using $O(V + E)$ and for Dijkstra's using $O(E \log_2 V)$.
2. In a complete graph with V vertices, the number of edges is $E = \frac{V(V-1)}{2}$. What is the Big-O complexity of B-F-S in terms of V only for a complete graph?
3. You have a choice between an algorithm that runs in $O(V^2)$ and one that runs in $O(E \log V)$. If the graph is very sparse ($E \approx V$), which one is better as V becomes very large?

Solutions

1. A graph has $V = 5000$ vertices and $E = 20000$ edges. Calculate the approximate number of operations for B-F-S using $O(V + E)$ and for Dijkstra's using $O(E \log_2 V)$.
 - For B-F-S, the cost is $5000 + 20000 = 25000$ operations.
 - For Dijkstra's, $\log_2(5000)$ is approximately 12.28.
 - The cost is $20000 \times 12.28 \approx 245600$ operations.

Answer: B-F-S: 25,000; Dijkstra: $\approx 245,600$

2. In a complete graph with V vertices, the number of edges is $E = \frac{V(V-1)}{2}$. What is the Big-O complexity of B-F-S in terms of V only for a complete graph?
 - The general cost is $O(V + E)$.
 - Substitute $E = \frac{V^2 - V}{2}$.
 - The expression becomes $O(V + \frac{V^2 - V}{2})$, which is dominated by the V^2 term.

Answer: $O(V^2)$

3. You have a choice between an algorithm that runs in $O(V^2)$ and one that runs in $O(E \log V)$. If the graph is very sparse ($E \approx V$), which one is better as V becomes very large?
 - If $E \approx V$, the second algorithm runs in $O(V \log V)$.
 - We compare V^2 with $V \log V$.
 - Since $\log V$ grows much slower than V , $V \log V$ is asymptotically smaller than V^2 .

Answer: $O(E \log V)$